

MICROWAVE GENERATOR

GENHRS2.0

2.0KW/2450MHZ



SPECIFICATIONS

FREQUENCY	2450MHZ	CONTROLS	PUSHBUTTONS: MICROWAVE ON MICROWAVE OFF RESET
HF-OUTPUT	2000W MAX WITH A MATCHED LOAD OUTPUT: 10-100% VARIABLE		INDICATOR LAMP: LINE VOLTAGE FAILURE
MAGNETRON	2M259 PANASONIC W/ ANODE VOLTAGE -4000V ANODE CURRENT 725MA		LED'S: INTERLOCK FILAMENT STAND BY OVERLOAD REMOTE COOLING FAULT
WAVEGUIDE	R26 (WR340)		
COOLANT	3L/MIN, 2 BAR		
MAINS	230V/60Hz/20.5A OTHERS AVAILABLE UPON REQUEST		
EXTERNAL INTERFACE	CONNECTOR X3; SUB-D 25-PIN MALE	DISPLAYS	FORWARD POWER REFLECTED POWER
SIZE	POWER SUPPLY 19" RACK; 4 UNITS TALL; 450MM DEEP HEAD CLOSED BOX; WATER COOLED; 390MM L x 160MM W x 200MM H	PWR CONTROL	POTENTIOMETER